

Amateur Mobiles

**ICOM**



www.pcimiami.com
+1 (305) 822-2258


PORTABLE COMMUNICATIONS, INC
"A Trusted Partner"

2300H

2M Mobile Transceiver

SPECS

Frequencies:	TX 144-148MHz RX 136-174MHz* *Guaranteed range 144-148MHz
Receiver System:	Double conversion superheterodyne
Modes:	FM, FM-N
Output Power:	65W, 25W, 10W, 5W
Channels:	207 (including 6 scan edges and 1 call channel)
Weight:	2.43lb
Number in Case:	4
Warranty:	1 Year



FEATURES

- Powerful 4.5W audio output
- Built-in CTCSS/DTCS encoder/decoder
- Multiple scan functions
- Wide/narrow channel setting
- Power supply voltage display
- DTMF autodial
- Repeater lockout
- Time-out timer
- Automatic power off
- S-meter squelch
- Selectable LCD backlight color (amber, yellow or green)
- Squelch attenuator

SUPPLIED ACCESSORIES

- Remote control microphone (HM133V)
- Microphone hanger
- Mobile mounting bracket kit
- DC power cable (OPC1132)
- Spare fuses
- Owner's manual

2730A

VHF/UHF Dual Band Transceiver

SPECS

Frequencies*:	Transmit: 144-148, 430-450MHz Receiver: 118-174, 375-550MHz *Guaranteed range: 144-148, 430-450MHz
Modes:	F2D, F3E
Output Power:	50/15/5W
Channels:	1052 (incl. 50 scan edges and 2 call)
Weight:	Main unit: 2.65lb Controller: 4.94oz
Number in Case:	5
Warranty:	1 Year



FEATURES

- Bluetooth® headset for hands free communication and remote control of the radio with three programmable buttons
- Multiple mounting options
- V/U, U/U simultaneous receive capability
- Independent controls for each band
- Durable PA module, 50W output power for VHF and UHF bands
- 104 DTCS and 50 CTCSS tone codes
- Split tone function allows you to encode and decode different CTCSS/DTCS tones
- Squelch delay and squelch attenuator
- Sub band auto mute function
- Sub band busy beep function
- Auto repeater functions
- Auto power off
- Time-out-timer
- 16 DTMF auto dial memories
- Weather channel receive with weather alert
- CI-V remote control capability

SUPPLIED ACCESSORIES

- Hand microphone (HM207)
- DC power cable (OPC345A)
- Controller cable (OPC837, 11.4ft)
- Microphone hanger
- Spare fuses
- Owner's manual

ID5100A

D-Star Dual Band Digital Transceiver

SPECS

Frequencies:	TX 144-148, 430-450MHz RX 118-174, 375-550MHz
Type of Emission:	F2D, F3E, F7W
Modes:	FM, FM-N, DV, AM (receive only) depending on version)
Output Power:	50W, 15W, 5W selectable
Channels:	1000 regular channels, 4 call channels, 50 program scan edges and 1200 repeater memories
Dimensions (W x H x D):	
Main Unit:	5.91x1.57x6.8in
Controller:	7.17x3.21x0.97in
Weight:	
Main Unit:	2.87lb
Controller:	9.17oz
Warranty:	1 Year



FEATURES

- Intuitive touch screen operation
- V/U, V/V, U/U Dual receive
- DV Dualwatch
- GPS receiver
- DV/FM Repeater list function
- Dplus reflector linking
- Built-in CTCSS/DTCS encoder and decoder
- Bluetooth options
- Send pictures over DV mode
- Menu-driven user interface
- Convenient memory contents management using CSV data format
- Speech function announces operating frequency, mode and received callsign (DV mode)
- Enhanced D-PRS functions with object, position, item and weather formats

SUPPLIED ACCESSORIES

- Hand microphone (HM-207)
- Controller cable (OPC1154A 3.5M; 11.4ft)
- Microphone hanger
- CD (CS-5100 and instruction handbook PDF)
- Spare fuse
- Owner's manual