

Mobiles

**ICOM**



www.pcimiami.com
+1 (305) 822-2258


PORTABLE COMMUNICATIONS, INC
"A Trusted Partner"

F5011 - F6011 Series

Basic Analog Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	8 with 2 zones
Channel Spacing:	12.5kHz
Programmable Keys:	4
Mil Spec:	810 C, D, E
Scan:	Normal, priority & dual priority



FEATURES

Priority scan function allows you to monitor one or two priority channels while scanning other non-priority channels
Tx channel and talk back functions allow you to make a quick response while scanning
4W speaker
Microphone hanger action programmable
Time out timer, lock-out penalty timer
Talk around function
Power-on password
Nuisance delete function

SIGNALING

CTCSS / DCS Encode/Decode

DTMF Encode

2/5 Tone

- Up to 10 2-tone codes can be decoded on a channel
- Up to 8 5-tone codes can be decoded on a channel

MDC1200

- PTT ID(Tx)
- Emergency call (Tx)
- Radio check (Rx)
- Stun/revive (Rx)

DTMF decode & autodial: UT-108R

COMES WITH

Microphone (HM-152)
Mounting bracket (F121 MMB)
Power cable (OPC-1132)
Owner's manual
Warranty: 2 years

ENCRYPTION

Simple Inversion: UT-109R 32 Codes
Rolling Code: UT-110R 1020 Codes



F5021 - F6021 Series

Advanced Analog Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	128 channels, 8 zones
Channel Spacing:	12.5 kHz
Display:	LCD with 8 character alphanumeric
Programmable Keys:	6
Mil Spec:	810 C, D, E, F
Scan:	Normal & priority



FEATURES

External memory channel control w/ optional ACC cable
Tx channel setting & talk back function
Radio kill, stun, revive
Embedded ESN
Mode dependent scan
Lone worker function
Power-on password
Nuisance delete function

SIGNALING

CTCSS / DCS Encode/Decode
2/5 Tone Encode/Decode

- Up to 10 2-tone codes can be decoded on a channel
- Up to 8 5-tone codes can be decoded on a channel
- Programmable items for codes: Beep sound, Answer back, Scan, Bell icon, Radio stun/kill

MDC1200

- PTT ID (Tx/Rx)
- Radio stun (Rx)
- Emergency TX/RX
- Radio check (Rx)
- Radio revive (Rx)
- 5 alias table

COMES WITH

Microphone (HM-152)
Mounting bracket
Power cable (OPC-1132)
Owner's manual
Warranty: 2 years

ENCRYPTION

Simple Inversion: UT-109R 32 Codes
Rolling Code: UT-110R 1020 Codes



F5121D - F6121D Series

IDAS™ Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	128 with 8 zones
Channel Spacing:	12.5kHz; 6.25kHz Digital
LCD Display:	8 Character alphanumeric LCD with backlit or night time operation
Programmable Keys:	7
Mil Spec:	810 C, D, E, F
Scan:	Normal, priority & dual priority



FEATURES

General Features:

- Lone worker function
- Power-on password function
- Time out timer
- Mic hanger action programmable

Digital Features:

- IDAS™ conventional
- IDAS™ single-site trunking
- Digital / Analog mixed mode operation
- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 64 Radio Access Numbers (RAN)
- GPS receiver connection w/ optional OPC-2078 ACC cable
- Programmable features:
 - PTT ID
 - RAN (radio access number)
 - Individual/talkgroup list (max 500)
 - SDM (short data message)
 - Remote monitor (Rx)
 - Digital voice scrambler
 - Call alert, stun/kill/revive (Rx), Emergency
 - Status, Radio check (Rx)

COMES WITH

Microphone (HM-152)
Mounting bracket kit
DC Power cable (OPC-1132)
Owner's manual
Warranty: 2 years

SIGNALING

2/5 Tone in analog mode
CTCSS/DTCS encoder/decoder (analog only)
DTMF Encode
DTMF Decode: UT-108R
MDC1200

- PTT ID
- Emergency
- Radio check (Rx)
- Stun/revive (Rx)
- 500 alias table



F5220D - F6220D Series

IDAS Trunking Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512
Output Power:	50W (VHF); 45W (UHF)
Channels:	128 with 8 zones
Channel Spacing:	15 / 12.5 / 6.25kHz
Mil Spec:	MIL 810
Scan:	Priority/Vote/Roaming
Weight:	2.4lb



FEATURES

General Features:

- Channel announcement
- CTCSS/DTCS encoder/decoder
- Microphone hanger action programmable
- Power-on password function
- Talk around function
- Voting scan
- Nuisance delete function
- Time-out-timer, lock-out penalty

Digital Features:

- IDAS™ conventional
- IDAS multi-site and single-site trunking and IDAS multi-site conventional
- Up to 500 individual and up to 500 group ID aliases (Each for single-site/multi-site/conventional)
- PTT ID and ANI
- Call alert
- Status
- SDM (Short Data Message)
- Radio check (RX)
- RAN (Radio Access Number)
- Remote monitor (RX)
- Emergency

COMES WITH

Hand Microphone (HM-152)
Mounting bracket kit
DC Power cable (OPC-1132)
Owner's manual
Warranty: 2 years

F5061 - F6061 & F5061D - F6061D Series

Analog, LTR, or IDAS™ Digital Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	512 channels, 128 zones
Channel Spacing:	12.5kHz, 6.25kHz (D versions)
LCD Display:	Dot matrix, switchable 1 line 12 character or 2 line 24 character
Programmable Keys:	7
Mil Spec:	810 C, D, E
Scan:	Normal, priority & dual priority



FEATURES

General Features

- Basic LTR, Analog, Digital mixed mode
- Detachable front panel (req. separation kit)
- D-Sub accessory connector
- 8 DTMF autodial memories & ANI functions
- Power ON password
- Radio stun/kill
- Surveillance function (temp. turns LEDs off)
- Busy repeater lock out function

Digital Features:

- IDAS™ conventional
- IDAS multi-site and single-site trunking and IDAS multi-site conventional
- Voting mode scanning
- NXDN® Digital Air Interface
- Short & long data messages
- 64 Radio Access Numbers (RAN)
- Individual & group selective call
- Strongest site search
- Firmware upgrade over IP
- Configuration over IP

SIGNALING

CTCSS/DCS encode/decode
2/5 Tone
DTMF
ANI with 2/5 tone & DTMF
MDC1200

ENCRYPTION

Simple Inversion: UT-109R 32 Codes
Rolling Code: UT-110R 1020 Codes

COMES WITH

Microphone (HM-148G)
Mounting bracket
Power cable (OPC-1132)
Owner's manual
Warranty: 3 years

MULTITRUNK

IDAS™
ICOM DIGITAL ADVANCED SYSTEM



MDC 1200
Compatible

F5360D – F6360D Series

Analog and IDAS™ 12.5 kHz & 6.25 kHz Digital & Type-C Trunking

SPECS

Frequencies:	136-174, 400-470MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	512 channels, 128 zones
Channel Spacing:	12.5kHz, 6.25kHz
LCD Display:	Dot matrix, switchable 1 line 12 character or 2 line 24 character
Programmable Keys:	7
Mil Spec:	810 C, D, E
Scan:	Normal, priority & dual priority



FEATURES

General Features

- Analog, Digital mixed mode
- GPS built-in (requires GPS antenna)
- D-Sub accessory connector
- 8 DTMF autodial memories & ANI functions
- Power ON password
- Radio stun/kill
- Surveillance function (temp. turns LEDs off)
- Busy repeater lock out function
- Menu driven user interface

Digital Features:

- IDAS™ conventional
- IDAS Type C trunking
- NXDN® Digital Air Interface
- 64 Radio Access Numbers (RAN)
- Individual & group selective call
- Strongest site search
- Transparent data
- Over-the-air alias

SIGNALING

CTCSS/DCS encode/decode
DTMF
MDC1200

COMES WITH

Microphone (HM-148G)
Mounting bracket
Power cable (OPC-1132)
Owner's manual
Warranty: 3 years



F5400D – F6400D Series

VHF UHF Digital Mobile Transceiver

SPECS

Frequencies:	136-174, 380-470, 450-512MHz
Output Power:	50W (VHF), 45W (UHF)
Channels:	1024 channels w/128 zones
Channel Spacing:	12.5kHz, 6.25kHz
LCD Display:	High-resolution color with icons and characters
Programmable Keys:	7 (D); 5 (DS)
Mil Spec:	C, D, E, F, G
Weight:	3.3lb
Waterproof Rating:	IP55
Versions:	With full display With numeric number only



FEATURES

General Features

- Basic LTR® / Conventional / IDAS
- GPS built-in
- Bluetooth™ built-in
- Intuitive user interface
- High-resolution color LCD
- Digital voice recorder – record up to 500 hours with 32GB microSD card
- Safety features: emergency button, lone worker function, and power OFF emergency function
- AquaQuake™
- Audio equalizer*
- D-Sub 25-pin ACC connector
- 20W audio amplifier for connecting with external public address system

Digital Features:

- IDAS™ conventional
- IDAS single-site and multi-site Type D trunking (optional upgrade)
- IDAS single-site and multi-site Type C trunking (optional upgrade)*
- Voting mode scanning
- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- Individual & group selective call

COMES WITH

- Hand microphone (HM-220)
- Mounting bracket kit
- DC power cable
- Microphone hanger
- Owner's manual
- Warranty: 3 years

ANALOG SIGNALING

- 2-tone, 5-tone, CTCSS and DTCS built-in
- DTMF autodial and DTMF decode
- MDC1200 compatible

ENCRYPTION

- AES/DES UT-134
- Over-the-Air Rekeying (requires license)*

*Future Availability

MULTITRUNK

IDAS
ICOM DIGITAL ADVANCED SYSTEM

Meets
MIL-STD 810

MDC 1200
Compatible

F1721 - F2721/F2821 Series

High End Analog, P25 Conventional Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-512MHz
Output Power:	50W (VHF); 45W (UHF)
Channels:	256 with 32 zones
Channel Spacing:	12.5 / 25kHz
LCD Display:	Dot matrix, switchable 1 line 12 characters or 2 lines 24 characters
Programmable Keys:	5 (simple version) or 7 (10-key version)
Mil Spec:	810 C, D, E
Scan:	Normal, priority & dual priority
Versions:	Analog only (upgradeable to P25) P25 ready (D versions)



FEATURES

General Features

- Detachable front panel
- Radio stun / kill
- Tactical group function
- Built-in audio compander (analog only)
- 22W PA built-in
- Power-on password function

Digital P25 Features

- Interoperability with other manufacturer's P25 digital radios in conventional mode
- Compatible w/ both analog FM & P25 digital mode

SIGNALING

MDC1200

CTCSS/DCS encode/decode

DTMF decode

2/5 tone encode/decode

Enhanced MDC (optional on analog)

ANI with 2/5 tone & DTMF

COMES WITH

Hand mic (HM-148G)
External speaker (SP-22) for F2821
Mounting bracket kit
DC Power cable (OPC-1132)
Owner's manual
Warranty: 2-Year
3-Year ("D" series)

ENCRYPTION

Simple Inversion: UT-109 02 32 Codes
Rolling Code: UT-110 02 1020 Codes



F9511 - F9521 Series

P25 Trunking Mobiles

SPECS

Frequencies:	136-174, 400-470, 450-520MHz
Output Power:	50W or 110W (VHF), 50W (UHF)
Channels:	512 / 128 zones
Channel Spacing:	15/30 (analog), 12.5kHz (digital)
PLL Channel Spacing:	2.5, 3.125kHz
LCD Display:	Dot matrix with backlighting and 2 lines of 12 characters each
Programmable Keys:	5 (S) or 7 (T)
Mil Spec:	810 C, D, E
Scan:	Normal, priority & dual priority
Waterproof Rating:	IP54 dust-protection and splash proof (controller only)
Versions:	50W without a DTMF keypad 50W with DTMF keypad 110W with DTMF keypad



FEATURES

General Features:

- 100 individual ID and 250 talkgroup ID memories
- Detachable front panel
- Programmable ACC port for external control, dimmer and horn control
- Dual head capable with 110W version
- Tactical group function
- 22W PA function with BTL amplifier
- RX speaker functions
- Scan settings – dual priority, mode dependent, talk back and more
- Built-in audio compander (analog only)
- Radio stun/kill function (P25 digital only)

P25 Digital Features:

- P25 digital conventional
- P25 digital trunking option
- DVSI's AMBE+2™ vocoder
- Digital/analog mixed mode operation
- P25 OTAR option

Compliant Standards:

- TIA/EIA TSB 102. CAAB compliant
- NTIA VHF specification compliant
- FIPS 140-2 (level 1) certified AES encryption

COMES WITH

Microphone (HM-148G)
Mounting bracket
Power cable
Owner's manual
Warranty: 3 years

F9511T includes the SP-35
F9511HT includes the OPC-726, but requires
an external speaker

ENCRYPTION

DES: UT-128
AES/DES: UT-125
AES FIPS: UT-125 FIPS

SIGNALING

CTCSS/DTCS encorder & decoder (analog
only)
2 Tone encorder & decoder (analog only)
MDC1200 (analog only)
DTMF audiodial (analog only)

