O ICOM Marine Handhelds





www.pcimiami.com +1 (305) 822-2258

VHF Marine Transceiver

SPECS

5W, 1W Output Power: Waterproof Rating: IPX7 (submersible protection) Frequencies: Tx: 156.025-157.425MHz Rx: 156.050–163.275MHz Usable Channel Groups: INT, USA, CAN and WX Type of Emission: FM (16K0G3E) Current Drain (at 3.7V DC):Tx (High): 2.3A Rx (at AF max): 300mA/200mA Weight: 7.8oz Versions:

Marine blue, metallic gray, pearl white



COMES WITH

Battery charger (BC217SA) Belt clip (MB133) Antenna (FASC59V) Hand strap Owner's manual Warranty: 3 years

FEATURES

Float 'n flash USB charging 11 hours battery life Large LCD with simple user interface (30% larger than M24) 550mW audio output 4-step battery life indicator Dual/Tri-watch functions Weather channel with weather alert Instant access to Ch. 16 or programmable call channel Auto scan function Tag scan Favorite channel functions Monitor function opens noise squelch LCD auto backlighting AquaQuake draining function

IPX7

VHF Marine Transceiver

SPECS

| Output Power: | 6W, 1W w/BP252 |
|------------------------|--|
| Waterproof Rating: | 2W, 1W w/BP251 alkaline cells IP57 (dust-protection and |
| | waterproof protection) |
| Frequencies: | Tx: 156.025-157.425MHz |
| | Rx: 156.050-163.275MHz |
| Usable Channel Groups: | INT, USA, CAN, WX |
| Type of Emission: | FM (16K0G3E) |
| Current Drain: | Tx (at 6W output): 1.5A |
| | Rx (at AF max): |
| | Internal speaker 300mA |
| | External speaker 200mA |
| | Power save 10mA |
| Weight: | 10.4oz (with BP252) |



FEATURES _____

Clear voice + voice boost Floats AquaQuake draining function LOUD button Noise cancelling microphone Automatic volume adjustment Low power consumption Large buttons and slim dimensions Dual/Tri-watch functions 4-step battery life indicator Weather channel with weather alert Auto scan function Instant access to Ch 16 or Ch 9

COMES WITH

Battery pack (BP252) Battery charger (BC173) AC adapter (BC147) Belt clip (MB109) Antenna (FASc58V) Hand strap Owner's manual Warranty: 3 years





VHF Marine Transceiver

SPECS

Output Power: Waterproof Rating: Frequencies:

Usable Channel Groups:INT, USA, CAN, WXType of Emission:FM (16K0G3E)Current Drain:Tx (at 6W output): 1.5

Weight:

6W, 3W, 1W IPX8 (submersible) Tx: 156.025-157.425MHz Rx: 156.050-163.275MHz INT, USA, CAN, WX FM (16K0G3E) Tx (at 6W output): 1.5A Rx (Max.audio): 450mA/250mA 11.3oz (with BP245N)



FEATURES _____

Both Versions:

- Slim, hourglass body and wide viewing angle LCD
- IPX8 Submersible Plus™
- 700mW loud audio
- 6W RF output power
- AquaQuake[™] water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Auto power save function

Plus Version:

- Last call voice recording
- Bidirectional active noise cancelling

COMES WITH

Antenna (FAS64V) Battery pack (BP245N) Belt clip (MB103) Cigarette lighter cable (CP25H) Rapid charger (BC210) Hand strap Owner's manual Warranty: 3 years



VHF Marine Transceiver

SPECS

| 5W, 3W, 1W JIS7 |
|-------------------------|
| |
| 156.025-157.425MHz |
| 156.050-163.275MHz |
| 146.000-174.000MHz |
| INT, USA, CAN, WX |
| 22 LMR |
| |
| 16K0G3E (Wide) |
| 16K0F3E (Wide) |
| 8K50F3E (Narrow) |
| Tx (at 5W output): 1.6A |
| Rx (at AF max): 200mA |
| 9.9oz |
| |



FEATURES _____

Tough construction, superior waterproofing Simple operation 22 programmable channels for land use Auto WX scan and WX Alert function Simple Up/Down switches for operating channel selection Instant access to Ch. 16 and Ch. 9 (or call channel) Simple add/delete TAG scanning operation Powerful 5W output 2 step power saver 4 level battery indicator The self check function checks internal temperature, connected battery voltage (over voltage detection), and water intrusion

COMES WITH

Battery pack (BP227) Battery charger (BC152) AC adapter (BC147SA) Swivel belt clip Antenna (FAS59V) Hand strap Owner's manual Warranty: 3 years



M93D

VHF Marine Transceiver

SPECS

| Output Power: | 5W, 1W |
|------------------------|-------------------------------|
| Waterproof Rating: | IPX7 (waterproof protection) |
| Frequencies: | Tx: 156.025-157.425 MHz |
| | Rx: 156.050-163.275 MHz |
| Usable Channel Groups: | INT, USA, CAN, WX |
| Type of Emission: | FM (16K0G3E) |
| | DSC (16K0G2B) |
| Current Drain: | Tx (5W/1W output): 1.5A/700mA |
| | Rx (Inter SP/Exter SP Max |
| | audio): 450mA/259mA |
| Weight: | 11.2 oz (with BP275) |



FEATURES _____

Built-in Glass D DSC with a red rear button for distress calls Large LCD with full dot matrix display Float'n flash Active noise cancelling Built-in GPS Integrated GNSS receiver Soft keys to assign 19 functions AquaQuake[™] draining function Navigation function from current position to the specified waypoint 50 waypoint memories with alphanumeric name for navigation Weather channel receive with alert function Dual/Tri-Watch function for monitoring Ch. 16 and/or call channel Battery indicator shows remaining battery power in four levels Favorite channel function for quick access to often used functions

COMES WITH

Antenna (FASC59V) Battery pack (BP285) Battery charger (BC220) AC adapter (BC123SA) Cigarette lighter cable (CP25H) Belt Clip (MB-133) Hand strap Owner's manual Warranty: 3 years



GM1600

Survival Craft 2-Way VHF Radio

SPECS

Output Power: Frequencies:

Type of Emission: Current Drain:

Weight:

2W, 1W 156.300-156.875MHz Rx: 156.050-163.275MHz FM (16K0G3E) Tx 2W output: 1.0A 1W output: 0.7A Rx AF max: 200mA 13.6oz (with BP234)



FEATURES ____

Meets the strict environmental requirements for survival craft radio Optional high capacity Lithium battery, BP234, has superior low temperature Large keypad with positive button action Wide viewing angle LCD display One touch access to Channel 16 and call channel Highly visible yellow colored body Bright LED indicator on the top of panel Optional VOX headset for on-board use

COMES WITH

Battery pack (BP224) Battery pack (BP234) Battery charger (BC158) AC adapter (BC147SA) Belt clip (MB103Y) Antenna (FAS61V) Neck strap Owner's manual Warranty: 3 years