



Marine Single Side Band



www.pcimiami.com
+1 (305) 822-2258

PCI
PORTABLE COMMUNICATIONS, INC
"A Trusted Partner"

M802 EXPORT ONLY

HF Marine Transceiver

SPECS

Output Power:	150W, 60W, 20W PEP (Selectable)
Frequencies:	Tx: 1.6–2.9999, 4.0–4.9999, 6.0–6.9999, 8.0–8.9999, 12.0–13.9999, 16.0–17.9999, 18.0–19.9999, 22.0–22.9999, 25.0–27.5000MHz Rx: 0.5–29.9999MHz (continuous)
Channels:	1335 (max.) (160 programmable; 249 ITU SSB duplex; 721 ITU SSB simplex; 662 ITU FSK duplex; 160 e-mail; 21ITU 4MHz simplex; 31 ITU 8MHz simplex)
Type of Emission:	J3E (SSB), J2B (AFSK), F1B (FSK), A1A (CW), H3E (AM*) *Rx only
Current Drain:	Tx (Max power): 30A Rx (Max audio): 3.0A
Weight:	
Main unit	10.36lb
Controller	1.26lb
Speaker	0.81lb



FEATURES

- Standard 4x8 remote controller
- Large LCD with dot-matrix characters
- Easy to use in all conditions
- Built-in digital selective calling
- Digital signal processor advantage
- 150W (PEP) of powerful output
- One-touch e-mail access
- Automatic antenna tuner, AT140
- Wide band receive coverage
- Remote control mic allows you to select channels directly
- Accessory RS232C port allows connection of modem, etc.
- GPS input, NMEA 0183 version 3.01
- A headphone jack in front of the controller

COMES WITH

- Remote controller (RC25)
- Separation cable (16.4ft) (OPC1106)
- Hand microphone (HM135)
- External speaker (SP24)
- DC power cables (OPC1107A)
- Owner's manual
- Warranty: 2 years

M700PRO EXPORT ONLY

SSB Radio Telephone

SPECS

Output Power:	150W, 60W, 20W PEP (Selectable)
Frequencies:	
Receive	500kHz-29.99MHz
Transmit	1.6-2.9999, 4.0-4.9999, 6.0-6.9999, 8.0-8.9999, 12.0-13.9999, 16.0-17.9999, 18.0-19.9999, 22.0-22.9999, 25.0-27.5000MHz
Channels:	150 (max.; 3 groups of 50 channels each)
Type of Emission:	J3E (USB), LSB, H3T (AM), J2B (AFKSK), F1B (FSK), R3E, A1A (CW)
Weight:	17.2lb



FEATURES

Rugged 150 watt transceiver
150 memory channels
Selectable dual/tri watch
PC Programmable
Large LCD display

COMES WITH

Hand microphone (HM180)
Mounting bracket (SP24)
DC power cables (OPC568)
Owner's manual
Warranty: 2 years