


ICOM

Marine

Fixed Mount



www.pcimiami.com
+1 (305) 822-2258


PORTABLE COMMUNICATIONS, INC
"A Trusted Partner"

M200 EXPORT ONLY

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W (High, low)
Waterproof Rating:	IPX7 (submersible protection)
Frequencies:	Tx: 156.025–162.000MHz Rx: 156.025–162.025MHz
Usable Channel Groups:	USA, INT, CAN
Type of Emission:	FM (16K0G3E)
Current Drain:	Tx (at 25W output): 5.5A Rx (Max audio): 200mA
Weight:	1.7lb



FEATURES

- Dualwatch and tri-watch function
- Favorite channel function
- Built-in ultra-stable TCXO for reliable frequency stability
- Channel operation with the hand microphone
- Instant-access button for Channel 16 and call channel
- Priority scan and normal scan
- Built-in low voltage indicator
- Keypad backlighting

COMES WITH

- Hand microphone (HM164B)
- DC Power cable (OPC891A)
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7

M400BB

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz Ch. 70: 156.525MHz
Usable Channel Groups:	USA, INT, CAN, WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx (at 25W output): 5.5A Rx (Max audio): 3.5A
Weight:	1.83lb (M400BB) 14.1oz (HM195B/SW)



FEATURES

- Space-saving, two-piece configuration
- New intuitive user interface
- Active noise cancelling
- 10W loud audio, public address and foghorn
- Built-in class D DSC
- Common NMEA interface
- AIS target call with MA-500TR
- MarineCommander™ compatible
- AquaQuake™ water draining function
- Dual/tri-watch function for monitoring Ch.16 and/or call channel

COMES WITH

- Commandmic (HM195B/SW)
- DC Power cable
- Owner's manual
- Warranty: 3 years

IPX7

M324 – M324G

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W (High, low)
Waterproof Rating:	IPX7 (submersible protection)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz Ch. 70: 156.525MHz
Usable Channel Groups:	USA, INT, CAN and WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx (at 25W output): 5.5A Rx (AF max): 1.5A
Weight:	1200g; 2.65lb



FEATURES

- Built-in GPS receiver (M324G)
- Intuitive user interface
- Built-in Class D DSC capability (ITU-R M493-13)
- NMEA 0183 input/output for common GPS/NAV interface
- AIS Target Call with AIS Transponder, MA-500TR
- MarineCommander™ compatible
- NMEA 0183 connectivity
- Favorite channel function
- AquaQuake™ draining function
- Weather channels with alert function
- Dual/tri-watch function for monitoring Ch.16 and/or call channel
- Black and super white versions available
- Amber LCD and keypad backlighting

COMES WITH

- Hand microphone (HM-164B/SW)
- DC power cable (OPC-891A)
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7

M424G

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible protection)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz
Usable Channel Groups:	USA, CAN, INT, WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx 25W output: 5.5A Rx AF Max External SP: 5.0A Internal SP: 1.5A
Weight:	2.65lb



FEATURES

- Built-in GPS
- Active noise canceling
- 10W loud audio, public address and foghorn
- Built-in class D DSC
- Optional COMMANDMICIV™ HM195B/SW or HM195GB/GSW
- Common GPS/NAV interface
- MarineCommander™ compatible
- MA-500TR AIS transponder compatible
- AquaQuake™ water draining function
- Weather channel with alert function
- Dualwatch and Tri-watch functions for monitoring Ch.16 and/or call channel
- Priority and normal scan
- Built-in attenuator for local communication

COMES WITH

- Hand microphone (HM-205)
- DC power cable
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7

M506

VHF Marine Transceiver

SPECS

Output Power:	25W or 1W (at 13.8V DC)
Waterproof Rating:	IPX8
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz CH70: 156.525MHz AIS1, 2
Usable Channels:	USA, INT, CAN, and WX
Type of Emission:	16K0G3E (FM), 16K0G2B (DSC)
Current Drain:	Tx 25W output: 5.5A Rx AF Max External SP: 5.0A Internal SP: 1.5A
Weight	3.09lb



FEATURES

- Integrated AIS Receiver on specific versions
- NMEA 2000® and NMEA 0183 connectivity on specific versions
- Last call voice recording
- Active noise cancelling
- 25W two-way hailer
- Large LCD and intuitive user interface
- 80dB (typical) IMD and channel selectivity
- MA-500TR AIS transponder and Marine-Commander™ compatible
- Compatible with COMMANDMICIV™

COMES WITH

- Hand microphone (HM205B/RB)
- DC power cable
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years



M604 EXPORT ONLY

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible construction)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz
Usable Channel Groups:	USA, CAN, INT and WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx (at 25W output): 5.5A Rx (Max audio): 1.5A
Weight:	3.09lb



FEATURES

- Compatible with the new MA500TR – Class B AIS Transponder
- Compliant to new FCC Class D DSC Regulations
- Superior receiver performance
- Large LCD with dot-matrix characters
- 30 Watt 2-way hailer capability
- Built-in ITU Class-D DSC
- Position request and position report
- Improved GPS information indication
- Front and rear panel microphone connection
- RX speaker function
- Favorite channel function
- Dual/tri-watch function for monitoring Ch.16 and/or call channel
- 7 levels adjustable backlit display and keypad
- Optional voice scrambler, UT-112 for private communication
- Weather channels with weather alert function
- AquaQuake™ water draining function emits a vibrating sound and clears water away from the speaker grill

COMES WITH

- Hand microphone (HM126RB/RG)
- DC power cable (OPC1174)
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7



M605

VHF Marine Transceiver

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX8
Frequencies:	Tx: 156.025–161.600 MHz Rx: 156.025–162.000 MHz CH70: 156.525 MHz Ais1, 2: 161.975, 162.025 MHz
Usable Channel Groups:	USA, CAN, INT and WX
Type of Emission:	16K0G3E (FM), 16K0G2B (DSC)
Current drain:	Tx (at 25W output): 6.0A Rx (Maximum audio): 8.0A
Weight:	3.30lb
Versions:	Radio without AIS receiver Radio with AIS receiver



FEATURES

- 30W listen back hailer
- Built-in horn/foghorn
- GNSS antenna included
- Configuration flexibility
 - M605 + three COMMANDMICS
 - M605 + two COMMANDMICS + one Command Head
 - M605 + two Command Heads + one COMMANDMIC
- 4.3" wide color TFT LCD
- Night mode ensures readability in dark places
- Intuitive user interface
- NMEA2000™ and NMEA0183 connectivity
- Class D DSC
- Active noise cancelling
- Last call voice recording

COMES WITH

- Radio
- Hand microphone (HM-205RB)
- GNSS antenna (UX-241)
- PC power cable
- Mounting bracket kit
- Warranty: 3 years



GM600 EXPORT ONLY

VHF GMDSS Marine Transceiver

SPECS

Output Power:	25W 1W
Waterproof Rating:	IPX7 (submersible construction)
Frequencies:	Tx: 156.025–161.600MHz Rx: 156.025–162.000MHz DSC 156.525MHz
Usable Channel:	INT channels
Type of Emissions:	16K0G3E(FM) 16K0G2B(DSC)
Current Drain:	Tx (at 25W output): 3.3A Rx (Max audio): 2.0A
Weight (approx):	3.5lb



FEATURES

- Class A DSC
- Dedicated distress button
- Meets MED “wheel mark” requirements
- Meets ITU-R M.493-13 DSC
- 4.3” wide color TFT LCD
- Night mode ensures readability in dark places
- Intuitive user interface
- 10W audio when plugged into an external speaker
- Optional DC-DC converter

COMES WITH

- Radio
- Hand Microphone (HM-214V)
- DC power cable
- Mounting bracket kit
- Warranty: 3 years

IPX7